

Safety Data Sheet



C K Enterprises, Inc.
1204 SW Jefferson Street
Lee's Summit, Missouri 64081-9899
(816) 524-1304

Section 1. Chemical Product and Company Identification

Product Name CK Power Cling
Product Use Base Board Stripper
Product Code 6851-A20
Date of Issue 2/23/16
Supersedes -

Emergency Telephone Numbers
CHEMTREC- 1-800-424-9300

(For use only in the event of emergencies involving a spill, leak, fire, exposure, or accident involving chemicals)

Section 2. Hazards Identification

Emergency Overview

DANGER



Health Hazards

| | |
|------------------------------------|------------|
| Serious Eye damage /Eye irritation | Category 1 |
| Skin Corrosion/Skin Irritation | Category 1 |
| Acute Toxicity: oral | Category 4 |

Precautionary Statements:

| | |
|----------------|--|
| P102 | Keep out of reach of children |
| P103 | Read label before use. |
| P210 | Keep away from heat, sparks, open flames and hot surfaces – no smoking |
| P251 | Pressurized container: Do not pierce or burn even after use |
| P260 | Do not breathe dust/fume/gas/mist/vapors/spray. |
| P270 | Do not eat drink or smoke when handling this product |
| P264 | Wash hands thoroughly after handling. |
| P280 | Wear protective gloves, protective clothing, face protection and eye protection |
| P301+P330+P331 | IF SWALLOWED: rinse mouth. Do NOT induce vomiting. |
| P303+P361+P353 | IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower. |
| P304+P340 | IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing. |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P405 | Store locked up |
| P410+P412 | Protect from sunlight. Do not expose to temperatures exceeding 122°F. |
| P501 | Dispose of in accordance with all federal, state and local regulations |

Hazard Statements:

| | |
|------|---|
| H302 | Harmful if swallowed |
| H314 | Causes severe skin burns and eye damage |
| H313 | May be harmful in contact with skin |
| H318 | Causes serious eye damage |

Routes of Entry

Dermal, Oral, and Inhalation

Acute Effects:

Eyes Overexposure can cause redness and burning sensation
Skin Overexposure can cause defatting.
Inhalation Overexposure can cause irritation, headache, dizziness, nausea and loss of coordination.
Ingestion Nausea, vomiting and gastrointestinal distress. May be fatal if swallowed and enters airways.

Section 3. Composition/Information on Ingredients

| Name of Ingredients | CAS Number | % by Weight |
|---------------------------------|-------------------|--------------------|
| Water | 7732-18-5 | 52-92 |
| Butane | 106-97-8 | 3-6 |
| Ethylene glycol Monobutyl ether | 111-76-2 | 3-6 |
| Ethanolamine | 141-43-5 | 3-6 |
| Isobutane | 75-28-5 | 1-3 |
| Propane | 74-98-6 | 1-3 |

Section 4. First Aid Measures

Eye Contact Rinse cautiously with water for at least 15 minutes holding open eyelids. Remove contact lenses if present and easy to do. If irritation persists, get medical advice or attention.
Skin Contact Wash skin with soap and water for at least 15 minutes. Call a poison center or doctor if you feel unwell.
Inhalation Remove to fresh air. Call a poison center or doctor if you feel unwell.
Ingestion Rinse mouth. Do not induce vomiting. Immediately call a poison center or physician. If vomiting occurs, lie on your side in the recovery position. Never give anything orally to an unconscious person.

Section 5. Fire Fighting Measures

National Fire Protection Association (U.S.A)
(estimated rating)



Hazardous Combustion Products CO and CO₂
Extinguishing Media Water, fog, dry chemical or carbon dioxide
Unsuitable Extinguishing Media Water may be ineffective but can be used to cool containers
Fire Fighting Procedures Stop spill/release if it can be done without risk. Move undamaged containers if it can be done safely. Contents under pressure. Keep away from ignition sources and open flames. Exposure to extreme heat and flames can cause them to rupture often with violent force.

Section 6. Accidental Release Measures

Spill Clean Up Stop spill/release if it can be done without risk. Prevent spilled material from entering sewers, storm drains and waterways. Eliminate all ignition sources. Avoid contact with spilled material. Do not touch or walk through spilled material. Clean up immediately. Use absorbent sweeping compound to soak up material and put into suitable container for disposal.

Section 7. Handling and Storage

Handling and Storage For industrial use only. Keep away from children. Wash hands after use. Do not get in eyes, on skin or on clothing. Do not breathe in vapors. Do not eat, drink or smoke while using product. Store in a cool, dry place. Protect from sunlight. Empty containers retain residue that may be dangerous.

Section 8. Exposure Controls/Personal Protection**Exposure Limits**

| Product Name | OSHA PEL | NIOSH REL | AIHA WEEL | ACGIH TLV |
|--------------|----------|-----------|-----------|-----------|
| | | | | |

| | | | | |
|--|--------------|--------------|---|--------------|
| Butane (106-97-8) | - | 800ppm TWA | - | 1000ppm TWA |
| Ethylene glycol Monobutyl ether(111-76-2) | 50ppm TWA | 5ppm TWA | - | 20ppm TWA |
| Ethanolamine (141-43-5) | 3ppm TWA | 3ppm TWA | - | 3ppm TWA |
| Isobutane (75-28-5) | - | 800ppm TWA | - | - |
| Propane (74-98-6) | 1,000ppm TWA | 1,000ppm TWA | - | 2,500ppm TWA |

Engineering Controls Use in a well-ventilated area

Personal Protective Equipment (PPE)

Eyes Wear chemical splash goggles or safety glasses with side shield to avoid contact with eyes.

Body Wear neoprene or nitrile rubber gloves when handling. It is recommended to wear chemical resistant clothing to avoid contact with skin.

Respiratory Use a NIOSH approved respirator if TLV are reached or exceeded. When spraying more than one half can continuously or more than one can consecutively, use NIOSH approved respirator.

Section 9. Physical and Chemical Properties

| | | | |
|-------------------------|-------------------|------------------------------|-------------------|
| Physical State | Thick Foam | Explosive Limits | N/A |
| Color | N/A | %VOC | 20.00% |
| Odor | N/A | Vapor Density | Slower than ether |
| Odor Threshold | N/A | Density | 7.79029 lb/gal |
| pH | 11.5 | Solubility | Soluble |
| Freezing Point | N/A | Partition Coefficient | N/A |
| Boiling Point | N/A | Auto-Ignition Temp. | N/A |
| Flash Point | N/A | Decomposition Temp. | N/A |
| Evaporation Rate | Slower than ether | Viscosity | N/A |
| Flammability | Will not burn | Specific Gravity | N/A |

Section 10. Stability and Reactivity

| | |
|---|------------------------|
| Stability and Reactivity | Stable |
| Incompatibility | None known |
| Hazardous Polymerization | Will not occur |
| Hazardous Decomposition Products | CO and CO ₂ |
| Conditions to Avoid | High temperatures |

Section 11. Toxicological Information

| | |
|------------------------------|---|
| Routes of Entry | Dermal, oral and inhalation |
| Symptoms | See section 2 |
| Skin Irritant | Yes. Overexposure will cause defatting of the skin. |
| Eye Irritant | Yes. Overexposure will cause redness and burning. Causes serious eye damage |
| Sensitizers | Not determined |
| Mutagenicity | No information found |
| Carcinogenicity | IARC Monographs: CAS # 111-76-2 Group 3-Not classifiable as to its carcinogenicity to humans |
| Reproductive Toxicity | No information found |
| Target Organs | No information found |
| Aspiration Hazard | |

Acute Toxicity

Ethanolamine (CAS# 141-43-5)

| | | |
|---------------|---------------------|-----------------------|
| Dermal | LD50 (skin, rabbit) | 1mL/kg (1mL/kg) |
| Oral | LD50 (oral, rat) | 1720mg/kg (1720mg/kg) |

Inhalation No data found

Ethylene Glycol Monobutyl Ether (CAS# 111-76-2)

Dermal LD50 (skin, rabbit) 220mg/kg (220mg/kg)

Oral LD50 (oral, rat) 470mg/kg (470mg/kg)

Inhalation LC50 (inhalation, rat) 450ppm/4H (450ppm)

Propane (CAS# 74-98-6)

No data found on acute toxicity of propane

Isobutane (CAS#75-28-5)

Oral No data found

Inhalation LC50(inhalation, rat): 57pph/15M (570000ppm)

Dermal No data found

Butane (CAS# 106-97-8)

Oral No data

Inhalation LC50(inhalation, rat): 658gm/m3/4H (658000mg/m3)

Dermal No data

Section 12. Ecological Information

Environmental Effects No ecological information available

Section 13. Disposal Considerations

Waste Information Dispose of in accordance with all Federal, State and Local pollution control regulations.

Section 14. Transportation Information

| Regulatory Information | UN number | Proper Shipping Name | Classes | Packaging Group | Label Code |
|------------------------|-----------|----------------------|---------|-----------------|------------|
| DOT Classification | - | Consume Commodity | ORM-D | - | None |

Note: DOT Classification applies to most packaging sizes. For specific container size classifications or for size exceptions, refer to the Bill of Lading with your shipment.

Section 15. Regulatory Information

US Federal Regulations The following substances are listed as a toxic chemical and are subject to report under the SARA act Section 313: None

The following substances have CERCLA reportable quantity values (in pounds):

None

Propane (CAS # 74-98-6) CAA 112(r) TQ listed: 10,000

Isobutane (CAS # 75-28-5) CAA 112(r) TQ listed: 10,000

Butane (CAS# 106-97-8)CAA 112(r) TQ listed: 10,000

State Regulations None

Section 16. Other Information

Last Revision 2/23/2016

The information contained herein is based on the data available to us and is believed to be accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. We assume no responsibility for injuries from the use of the product described herein.