

Safety Data Sheet



C K Enterprises, Inc.
1204 SW Jefferson Street
Lee's Summit, Missouri 64081-9899
(816) 524-1304

Section 1. Chemical Product and Company Identification

Product Name CK Ultra Shine
Product Use Clear coating
Product Code 6903-A20
Date of Issue 3/3/2016
Supersedes -

Emergency Telephone Numbers
CHEMTREC- 1-800-424-9300

(For use only in the event of emergencies involving a spill, leak, fire, exposure, or accident involving chemicals)

Section 2. Hazards Identification

Emergency Overview

DANGER



Health Hazards

Skin Corrosion/Irritation	Category 2
Serious eye damage/ eye irritation	Category 2A
Specific Target Organ Toxicity, single exposure; Narcotic Effects	Category 3
Specific Target Organ Toxicity, Repeated Exposure	Category 2
Aspiration Hazard	Category 1
Reproductive Toxicity	Category 2

Physical Hazards

Flammable Aerosol	Category 1
-------------------	------------

Precautionary Statements:

P102	Keep out of reach of children
P201	Obtain special instructions before use
P202	Do not handle until all safety precautions have been read and understood
P210	Keep away from heat, sparks, open flames and hot surfaces – no smoking
P211	Do not spray on an open flame or other ignition sources
P251	Pressurized container: Do not pierce or burn even after use
P261	Avoid breathing dust/fume/gas/mist/vapors/spray.
P264	Wash hands thoroughly after handling
P271	Use outdoors or in a well-ventilated area
P280	Wear protective gloves, clothing and eye protection
P301+P310	IF SWALLOWED: immediately call a poison center or physician if you feel unwell.
P312	Call a POISON CENTER or doctor /physician if you feel unwell
P331	Do not induce vomiting
P302+P352	IF ON SKIN: Wash with plenty of soap and water
P304+P340	IF INHALED: Remove victim to fresh air and keep in a recovery position comfortable for breathing
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention
P332+P313	IF skin irritation occurs: Get medical advice/attention
P337+P313	IF eye irritation persists: Get medical advice/attention
P362	Remove contaminated clothing and wash before reuse
P370+P378	In case of fire: use water fog, dry chemical or carbon dioxide to extinguish
P391	Collect spillage. Hazardous to the aquatic environment.
P403+P235	Store in a well-ventilated area. Keep cool.

P405 Store locked up
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 122°F
 P501 Dispose of in accordance with all federal, state and local regulations

Hazard Statements:

H222 Extremely flammable aerosol
 H304 May be fatal if swallowed and enters airways
 H315 Causes skin irritation
 H319 Causes serious eye irritation
 H336 May cause drowsiness or dizziness
 H361 Suspected of damaging fertility or the unborn child
 H373 Causes damage to organs through prolonged or repeated exposure

Routes of Entry Dermal, Oral, and Inhalation**Acute Effects:**

Eyes Causes serious eye irritation. Overexposure can cause redness and burning sensation.
Skin Causes skin irritation. Overexposure will cause defatting of skin.
Inhalation Causes irritation, nausea, headache, dizziness and loss of coordination. Overexposure can cause unconsciousness and even death.
Ingestion Nausea, vomiting and gastrointestinal distress

Section 3. Composition/Information on Ingredients

<u>Name of Hazardous Ingredients</u>	<u>CAS Number</u>	<u>% by Weight</u>
Hexane	110-54-3	29-52
Butane	106-97-8	8-18
Isobutane	75-28-5	4-9
Propane	74-98-6	18-32
Silicone	63148-62-9	3-6

Section 4. First Aid Measures

Eye Contact Rinse cautiously with water for at least 15 minutes holding open eyelids. Remove contact lenses if present and easy to do. If irritation persists, get medical advice or attention.
Skin Contact Remove all contaminated clothing; wash before reuse. Wash skin with water for at least 15 minutes. Call a poison center or doctor if you feel unwell.
Inhalation Remove to fresh air. Call a poison center or doctor if you feel unwell.
Ingestion Rinse mouth. Do not induce vomiting. Immediately call a poison center or physician. If vomiting occurs, lie on your side in the recovery position. Never give anything orally to an unconscious person.

Section 5. Fire Fighting Measures

National Fire Protection Association (U.S.A)
 (estimated rating)



Hazardous Combustion Products CO and CO₂
Extinguishing Media Water, fog, dry chemical or carbon dioxide
Unsuitable Extinguishing Media Water may be ineffective but can be used to cool containers
Fire Fighting Procedures Stop spill/release if it can be done without risk. Move undamaged containers if it can be done safely. Contents under pressure. Keep away from ignition sources and open flames. Exposure to extreme heat and flames can cause them to rupture often with violent force.

Section 6. Accidental Release Measures

Spill Clean Up Stop spill/release if it can be done without risk. Prevent spilled material from entering sewers, storm drains and waterways. Eliminate all ignition sources. Avoid contact with spilled material. Do not touch or walk

through spilled material. Clean up immediately. Use absorbent sweeping compound to soak up material and put into suitable container for disposal.

Section 7. Handling and Storage

Handling and Storage For industrial use only. Keep away from children. Always wear appropriate personal protective equipment when handling. Wash hands after use. Do not get in eyes, on skin or on clothing. Do not breathe in vapors. Do not eat, drink or smoke while using product. Store in a cool, dry place. Protect from sunlight. Empty containers retain residue that may be dangerous.

Section 8. Exposure Controls/Personal Protection

Exposure Limits

Product Name	OSHA PEL	NIOSH REL	AIHA WEEL	ACGIH TLV
Hexane (110-54-3)	500ppm	50ppm	-	50ppm
Butane (106-97-8)	-	800ppm	-	1,000ppm
Isobutane (75-28-5)	-	800ppm	-	-
Propane (74-98-6)	1,000ppm	1,000ppm	-	2,500ppm

Engineering Controls Use in a well-ventilated area



Personal Protective Equipment (PPE)

Eyes Chemical splash goggles
Body Rubber or neoprene gloves, long sleeved shirt and pants
Respiratory Use a NIOSH approved respirator if TLV are reached or exceeded

Section 9. Physical and Chemical Properties

Physical State	Aerosol	Explosive Limits	Upper: 9.5 Lower: 1.8
Color	N/A	Vapor Pressure	N/A
Odor	Characteristic	Vapor Density	Slower than ether
Odor Threshold	N/A	Density	41.37173 lb/gal
pH	N/A	%VOC	94.99041%
Freezing Point	N/A	Partition Coefficient	N/A
Boiling Point	High: 610°F Low: 0°F	Auto-Ignition Temp.	N/A
Flash Point	<73°F	Decomposition Temp.	N/A
Evaporation Rate	Slower than ether	Viscosity	N/A
Flammability	Flashpoint below 73°F	Specific Gravity	N/A

Section 10. Stability and Reactivity

Stability and Reactivity	Stable
Incompatibility	None known
Hazardous Polymerization	Will not occur
Hazardous Decomposition Products	CO and CO ₂
Conditions to Avoid	High temperatures

Section 11. Toxicological Information

Routes of Entry	Dermal, oral and inhalation
Skin Irritant	Yes

Eye Irritant	Yes
Sensitizers	Not determined
Mutagenicity	No information found
Carcinogenicity	None
Reproductive Toxicity	Suspected of damaging fertility or the unborn child
Target Organs	May cause drowsiness or dizziness (Category 3) May cause damage to organs through prolonged or repeated exposure (Category 2)
Aspiration Hazard	May be fatal if swallowed and enter airways (Category 1)

Acute Toxicity**Hexane CAS# 110-54-3**

Dermal	No LD50 data		
Oral	LD50	(oral, rat)	25gm/kg (25000mg/kg)
Inhalation	LC50	(inhalation, rat)	48000ppm/4H (48000ppm)

Butane CAS# 106-97-8

Dermal	No data		
Oral	No data		
Inhalation	LC50	(inhalation, rat)	658gm/m3/4H (658000mg/m3)

Propane (CAS# 74-98-6)

No data found on acute toxicity of propane	
--	--

Isobutane (CAS#75-28-5)

Oral	No data found		
Inhalation	LC50(inhalation, rat): 57pph/15M (570000ppm)		
Dermal	No data found		

Silicone(CAS # 63148-62-9)

Oral	LD50	oral, rat	> 17gm/kg (17000mg/kg)
Inhalation	No LD50 data found		
Dermal	LD50	skin, rabbit	> 2gm/kg (2000mg/kg)

Section 12. Ecological Information

Environmental Effects Toxic to aquatic life with long lasting effects

Section 13. Disposal Considerations

Waste Information Dispose of in accordance with all Federal, State and Local pollution control regulations.

Section 14. Transportation Information

Regulatory Information	UN number	Proper Shipping Name	Classes	Packaging Group	Label Code
DOT Classification	-	Consumer Commodity	ORM-D	-	None

Note: DOT Classification applies to most packaging sizes. For specific container size classifications or for size exceptions, refer to the Bill of Lading with your shipment.

Section 15. Regulatory Information

US Federal Regulations The following substances are listed as a toxic chemical and are subject to report under the SARA act Section 313:

Hexane	110-54-3	11-27%
--------	----------	--------

The following substances have CERCLA reportable quantity values (in pounds):

Hexane	110-54-3	5,000
---------------	-----------------	--------------

Propane (CAS # 74-98-6) CAA 112(r) TQ listed: 10,000
Isobutane (CAS # 75-28-5) CAA 112(r) TQ listed: 10,000
Butane (CAS# 106-97-8)CAA 112(r) TQ listed: 10,000

State Regulations None

Section 16. Other Information

Last Revision 3/3/2016

The information contained herein is based on the data available to us and is believed to be accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. We assume no responsibility for injuries from the use of the product described herein.