

# Safety Data Sheet



C K Enterprises, Inc.  
1992 NW US 50 Highway  
Lone Jack, Missouri 64070  
(816) 524-1304

## Section 1. Chemical Product and Company Identification

**Product Name** CK Power Cling  
**Product Use** Base Board Stripper  
**Product Code** 6851-A20  
**Date of Issue** 9/22/2020  
**Supersedes** -

**Emergency Telephone Numbers**  
**CHEMTREC- 1-800-424-9300**

(For use only in the event of emergencies involving a spill, leak, fire, exposure, or accident involving chemicals)

## Section 2. Hazards Identification

### Emergency Overview

**DANGER**



### **Health Hazards**

Serious Eye damage /Eye irritation	Category 1
Skin Corrosion/Skin Irritation	Category 1
Acute Toxicity: oral	Category 4

### Precautionary Statements:

P102	Keep out of reach of children
P103	Read label before use.
P210	Keep away from heat, sparks, open flames and hot surfaces – no smoking
P251	Pressurized container: Do not pierce or burn even after use
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P270	Do not eat drink or smoke when handling this product
P264	Wash hands thoroughly after handling.
P280	Wear protective gloves, protective clothing, face protection and eye protection
P301+P330+P331	IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P405	Store locked up
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 122°F.
P501	Dispose of in accordance with all federal, state and local regulations

### Hazard Statements:

H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H313	May be harmful in contact with skin
H318	Causes serious eye damage

### Routes of Entry

**Dermal, Oral, and Inhalation**

**Acute Effects:**

**Eyes** Overexposure can cause redness and burning sensation  
**Skin** Overexposure can cause defatting.  
**Inhalation** Overexposure can cause irritation, headache, dizziness, nausea and loss of coordination.  
**Ingestion** Nausea, vomiting and gastrointestinal distress. May be fatal if swallowed and enters airways.

**Section 3. Composition/Information on Ingredients**


<u>Name of Ingredients</u>	<u>CAS Number</u>	<u>% by Weight</u>
Water	7732-18-5	52-92
Butane	106-97-8	3-6
Ethylene glycol Monobutyl ether	111-76-2	3-6
Ethanolamine	141-43-5	3-6
Isobutane	75-28-5	1-3
Propane	74-98-6	1-3

**Section 4. First Aid Measures**

**Eye Contact** Rinse cautiously with water for at least 15 minutes holding open eyelids. Remove contact lenses if present and easy to do. If irritation persists, get medical advice or attention.  
**Skin Contact** Wash skin with soap and water for at least 15 minutes. Call a poison center or doctor if you feel unwell.  
**Inhalation** Remove to fresh air. Call a poison center or doctor if you feel unwell.  
**Ingestion** Rinse mouth. Do not induce vomiting. Immediately call a poison center or physician. If vomiting occurs, lie on your side in the recovery position. Never give anything orally to an unconscious person.

**Section 5. Fire Fighting Measures**

National Fire Protection Association (U.S.A)  
(estimated rating)



**Hazardous Combustion Products** CO and CO<sub>2</sub>  
**Extinguishing Media** Water, fog, dry chemical or carbon dioxide  
**Unsuitable Extinguishing Media** Water may be ineffective but can be used to cool containers  
**Fire Fighting Procedures** Stop spill/release if it can be done without risk. Move undamaged containers if it can be done safely. Contents under pressure. Keep away from ignition sources and open flames. Exposure to extreme heat and flames can cause them to rupture often with violent force.

**Section 6. Accidental Release Measures**

**Spill Clean Up** Stop spill/release if it can be done without risk. Prevent spilled material from entering sewers, storm drains and waterways. Eliminate all ignition sources. Avoid contact with spilled material. Do not touch or walk through spilled material. Clean up immediately. Use absorbent sweeping compound to soak up material and put into suitable container for disposal.

**Section 7. Handling and Storage**

**Handling and Storage** For industrial use only. Keep away from children. Wash hands after use. Do not get in eyes, on skin or on clothing. Do not breathe in vapors. Do not eat, drink or smoke while using product. Store in a cool, dry place. Protect from sunlight. Empty containers retain residue that may be dangerous.

**Section 8. Exposure Controls/Personal Protection****Exposure Limits**

Product Name	OSHA PEL	NIOSH REL	AIHA WEEL	ACGIH TLV

Butane (106-97-8)	-	800ppm TWA	-	1000ppm TWA
Ethylene glycol Monobutyl ether( 111-76-2)	50ppm TWA	5ppm TWA	-	20ppm TWA
Ethanolamine (141-43-5)	3ppm TWA	3ppm TWA	-	3ppm TWA
Isobutane (75-28-5)	-	800ppm TWA	-	-
Propane (74-98-6)	1,000ppm TWA	1,000ppm TWA	-	2,500ppm TWA

**Engineering Controls** Use in a well-ventilated area

#### Personal Protective Equipment (PPE)

**Eyes** Wear chemical splash goggles or safety glasses with side shield to avoid contact with eyes.  
**Body** Wear neoprene or nitrile rubber gloves when handling. It is recommended to wear chemical resistant clothing to avoid contact with skin.  
**Respiratory** Use a NIOSH approved respirator if TLV are reached or exceeded. When spraying more than one half can continuously or more than one can consecutively, use NIOSH approved respirator.

#### Section 9. Physical and Chemical Properties

<b>Physical State</b>	Thick Foam	<b>Explosive Limits</b>	N/A
<b>Color</b>	N/A	<b>%VOC</b>	20.00%
<b>Odor</b>	N/A	<b>Vapor Density</b>	Slower than ether
<b>Odor Threshold</b>	N/A	<b>Density</b>	7.79029 lb/gal
<b>pH</b>	11.5	<b>Solubility</b>	Soluble
<b>Freezing Point</b>	N/A	<b>Partition Coefficient</b>	N/A
<b>Boiling Point</b>	N/A	<b>Auto-Ignition Temp.</b>	N/A
<b>Flash Point</b>	N/A	<b>Decomposition Temp.</b>	N/A
<b>Evaporation Rate</b>	Slower than ether	<b>Viscosity</b>	N/A
<b>Flammability</b>	Will not burn	<b>Specific Gravity</b>	N/A

#### Section 10. Stability and Reactivity

<b>Stability and Reactivity</b>	Stable
<b>Incompatibility</b>	None known
<b>Hazardous Polymerization</b>	Will not occur
<b>Hazardous Decomposition Products</b>	CO and CO <sub>2</sub>
<b>Conditions to Avoid</b>	High temperatures

#### Section 11. Toxicological Information

<b>Routes of Entry</b>	Dermal, oral and inhalation
<b>Symptoms</b>	See section 2
<b>Skin Irritant</b>	Yes. Overexposure will cause defatting of the skin.
<b>Eye Irritant</b>	Yes. Overexposure will cause redness and burning. Causes serious eye damage
<b>Sensitizers</b>	Not determined
<b>Mutagenicity</b>	No information found
<b>Carcinogenicity</b>	IARC Monographs: CAS # 111-76-2 Group 3-Not classifiable as to its carcinogenicity to humans
<b>Reproductive Toxicity</b>	No information found
<b>Target Organs</b>	No information found
<b>Aspiration Hazard</b>	

#### Acute Toxicity

##### Ethanolamine (CAS# 141-43-5)

<b>Dermal</b>	LD50 (skin, rabbit)	1mL/kg (1mL/kg)
<b>Oral</b>	LD50 (oral, rat)	1720mg/kg (1720mg/kg)
<b>Inhalation</b>	No data found	

**Ethylene Glycol Monobutyl Ether (CAS# 111-76-2)**

**Dermal** LD50 (skin, rabbit) 220mg/kg (220mg/kg)  
**Oral** LD50 (oral, rat) 470mg/kg (470mg/kg)  
**Inhalation** LC50 (inhalation, rat) 450ppm/4H (450ppm)

**Propane (CAS# 74-98-6)**

No data found on acute toxicity of propane

**Isobutane (CAS#75-28-5)**

**Oral** No data found  
**Inhalation** LC50(inhalation, rat): 57pph/15M (570000ppm)  
**Dermal** No data found

**Butane (CAS# 106-97-8)**

**Oral** No data  
**Inhalation** LC50(inhalation, rat): 658gm/m3/4H (658000mg/m3)  
**Dermal** No data

**Section 12. Ecological Information**

**Environmental Effects** No ecological information available

**Section 13. Disposal Considerations**

**Waste Information** Dispose of in accordance with all Federal, State and Local pollution control regulations.

**Section 14. Transportation Information**

Regulatory Information	UN number	Proper Shipping Name	Classes	Packaging Group	Label Code
DOT Classification	-	Consume Commodity	ORM-D	-	None

Note: DOT Classification applies to most packaging sizes. For specific container size classifications or for size exceptions, refer to the Bill of Lading with your shipment.

**Section 15. Regulatory Information**

**US Federal Regulations** The following substances are listed as a toxic chemical and are subject to report under the SARA act Section 313: None

The following substances have CERCLA reportable quantity values (in pounds):

**None**

**Propane (CAS # 74-98-6) CAA 112(r) TQ listed: 10,000**  
**Isobutane (CAS # 75-28-5) CAA 112(r) TQ listed: 10,000**  
**Butane (CAS# 106-97-8)CAA 112(r) TQ listed: 10,000**

**State Regulations** None

---

**Section 16. Other Information**

**Last Revision** 9/22/2020

The information contained herein is based on the data available to us and is believed to be accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. We assume no responsibility for injuries from the use of the product described herein.